

DG3600E

CE EU-V

Frequency(Hz):	50	60
Rated AC Output(kW):	2.8	3.0
Max. AC Output(kW):	3.0	3.3
AC Output Voltage(V):	230;115/230	120;240;120/240
Noise Level LwA(4m)dB(A):	96	
Fuel Tank Capacity(L):	11.5	
Continuous Work(h):	9	8
Fuel Consumption(full load)g/kw.h:	< 285.6	
Alternator:	190x85/Copper Wire	
Net Weight/Gross Weight(kg):	77 / 80	
Dimension(LxWxH)(mm):	697x475x572	
20ft/40ft/40HQ Container Qty:	144 / 292 / 292	
Engine:	UD178	
Engine Type:	Single-cylinder,4-Stroke,Air-cooled Diesel Engine	
Displacement Capacity(cc):	296	
Max. Output(HP/rpm):	6.7/3600	
Lubricatopn Oil:	SAE10W40 API CF	
Lubricatopn Oil Volume(L):	1.1	

Peak watts
3300W



Recoil Electric

DG5500E

EMC CE EU-V

Frequency(Hz):	50	60
Rated AC Output(kW):	4.5	5.0
Max. AC Output(kW):	5.0	5.5
AC Output Voltage(V):	230;115/230	120;240;120/240
Noise Level LwA(4m)dB(A):	96	
Fuel Tank Capacity(L):	11.5	
Continuous Work(h):	6.5	5.5
Fuel Consumption(full load)g/kw.h:	< 285.7	
Alternator:	190x132/Copper Wire	
Net Weight/Gross Weight(kg):	98 / 140	
Dimension(LxWxH)(mm):	727x515x627	
20ft/40ft/40HQ Container Qty:	105 / 219 / 230	
Engine:	UD186	
Engine Type:	Single-cylinder,4-Stroke,Air-cooled Diesel Engine	
Displacement Capacity(cc):	418	
Max. Output(HP/rpm):	10/3600	
Lubricatopn Oil:	SAE10W40 API CF	
Lubricatopn Oil Volume(L):	1.65	

Peak watts
5500W



Recoil Electric

DIESEL GENERATORS

- Plenty of power.
- Over-sized noise reducing muffler has a built-in spark arrestor for safe use in mandated areas and jobsites.



> Silent Series ///

DG5500SE

EMC CE Noise EU-V

Frequency(Hz):	50	60
Rated AC Output(kW):	4.2	4.6
Max. AC Output(kW):	4.5	5.0
AC Output Voltage(V):	230;115/230	240;120/240
Noise Level LwA(4m)dB(A):	96	
Fuel Tank Capacity(L):	16	
Continuous Work(h):	7.3	6.2
Fuel Consumption(full load)g/kw.h:	< 285.7	
Alternator:	190x140/Copper Wire	
Net Weight/Gross Weight(kg):	141 / 150	
Dimension(LxWxH)(mm):	945x560x780	
20ft/40ft/40HQ Container Qty:	72 / 144 / 144	
Engine:	UD186	
Engine Type:	Single-cylinder,4-Stroke,Air-cooled Diesel Engine	
Displacement Capacity(cc):	418	
Max. Output(HP/rpm):	10/3600	
Lubricatopn Oil:	SAE10W40 API CF	
Lubricatopn Oil Volume(L):	1.65	

Peak watts
5000W



Recoil Electric

DG8000S

Frequency(Hz):	50	60
Rated AC Output(kW):	6.0	6.2
Max. AC Output(kW):	6.4	6.7
AC Output Voltage(V):	230;115/230	240;120/240
Noise Level LwA(4m)dB(A):	98	
Fuel Tank Capacity(L):	22	
Continuous Work(h):	9	
Fuel Consumption(full load)g/kw.h:	< 285.7	
Alternator:	190x148/Copper Wire	
Net Weight/Gross Weight(kg):	179 / 188	
Dimension(LxWxH)(mm):	1105x650x850	
20ft/40ft/40HQ Container Qty:	30 / 60 / 60	
Engine:	UD192	
Engine Type:	Single-cylinder,4-Stroke,Air-cooled Diesel Engine	
Displacement Capacity(cc):	498	
Max. Output(HP/rpm):	15/3600	
Lubricatopn Oil:	SAE10W40 API CF	
Lubricatopn Oil Volume(L):	1.65	

Peak watts
6700W



Recoil Electric

DG12000S

Frequency(Hz):	50	60
Rated AC Output(kW):	10	10
Max. AC Output(kW):	11	11
AC Output Voltage(V):	230	120/240
Noise Level LwA(4m)dB(A):	86	
Fuel Tank Capacity(L):	30	
Continuous Work(h):	86	
Fuel Consumption(full load)g/kw.h:	< 275	
Alternator:	245x145/Copper Wire	
Net Weight/Gross Weight(kg):	275 / 275	
Dimension(LxWxH)(mm):	1250x700x935	
20ft/40ft/40HQ Container Qty:	30 / 54 / 54	
Engine:	UD192	
Engine Type:	L-Twin,4-Stroke,Air-cooled, Diesel Engine	
Displacement Capacity(cc):	997	
Max. Output(HP/rpm):	19/3600	
Lubricatopn Oil:	SAE10W40 API CF	
Lubricatopn Oil Volume(L):	2.75	

Peak watts
11000W



Recoil Electric

Generators Selection Guide

EU 250V/16A	EU-Industrial 250V/32A	EU(3-phase) 415V/16A	AU 250V/15A	Universal Socket 250V/10A	Universal Socket(cover) 250V/15A
US 125V/30A	US 125V/20A	US(GFCI) 125V/20A	US 125V/20A	US(quadripuntal) 125V/250V/30A	AC post 415V/50A
DC Socket	DC post 120V/30A	Welding joints	ATS joint	ON-OFF	Volt.Switch
Breaker	Breaker	1P Breaker	2P Breaker	3P Breaker	
LB-45 Voltmeter	99T1 Voltmeter	HJ-301 Three in one	Timer		